IDS-2200

Intrusion Detection System IDS 1R2 Release Announcement

December 2011

Formula Consultants Inc. 100 S. Anaheim Blvd. Anaheim, CA 92815



CONFIDENTIAL AND PROPRIETARY PROPERTY

Subject to certain restrictions and non-disclosure requirements of Formula Consultants Incorporated.

Copyright Notice

Copyright © 2011 by Formula Consultants Incorporated, P.O. Box 544, Anaheim, California 92815.

No part of this material may be reproduced in any form without permission in writing from Formula Consultants Incorporated.

Formula Consultants Incorporated reserves the right to revise or modify the contents of this document. Contact Formula Consultants to verify that you have the most current revision of this document.

Direct your comments or requests to:

Formula Consultants Incorporated P. O. Box 544 Anaheim, California 92815 714/778-0123 714/778-6364 (Fax)

Software Version: 1R2

Contents

IDS-2200 LEVEL 1R2 RELEASE ANNOUNCEMENT	1
General	1
Product Overview	1
Release Description	2
Minor Enhancements	2
IDS-2200 Notes Of Interest	3
Restrictions and Limitations	4
Compatibility and Migration	4
Previous Level Support	4
Documentation	4
FCI Website	4
FCI Support Center	5
Corrections	5
Ordering Instructions General Releases	6
Ordering the Software	6
PRODUCT ORDER FORM	7

IDC	2200	Laval	1D2	Dalassa	Announcement

[Page intentionally left blank.]

IDS-2200 Level 1R2 Release Announcement

General

Intrusion Detection System 1R2 Now Available

Formula Consultants Incorporated is pleased to announce that Level 1R2 of IDS-2200 is now available for distribution. IDS-2200 is FCI's Intrusion Detection System used to monitor security events within the Unisys OS2200 environment.

The IDS-2200 level 1R2 product release can be obtained via the FCI Support Center (see Note of Interest number 1). Consistent with FCI policy, this release will be provided at no additional cost to all IDS-2200 users with current maintenance contracts, as well as to users who are still in their initial warranty period.

Product Overview

IDS-2200 can assist businesses facing additional security requirements by providing real-time security monitoring of the OS2200 environment.

IDS-2200 installs as a Security Agent or agents assigned to monitor major functional areas of your OS2200 operating environment. IDS also has one or more Client component(s), installed on a PC, with which administrators review information gathered by the Security Agents.

- The IDS Security Agent runs as a background job reading different system and product log files. The Security Agent collects information about security related events for any IDS-2200 Clients which are connected.
- The IDS Security Agent uses and connects to COMAPI. The Security Agent listens on a site-defined port for a valid IDS Client with which it can connect.

- The IDS Security Agent optionally encrypts communications with IDS clients using its own AES encryption or the Unisys CIPHER-API encryption product.
- The IDS Security Agent responds to conditions it detects, and performs Security Response Actions on behalf of the IDS Client. The actions to be taken are configured by an authorized administrator. Actions include, Disabling a UserID, Enabling a UserID and terminating all runs for a given UserID.
- The IDS-2200 Product also includes an optional Product Modification Element (PME) for MAPPER. This PME implements enhanced security logging for MAPPER which, in turn, allows IDS-2200 to monitor it.

Release Description

Stability Update and Minor Enhancement Release

IDS-2200 level 1R2 is a stability update and minor enhancement release.

Product Enhancements

IDS-2200 Power Client support of Windows 7

The IDS-2200 1R2 Power Client has been enhanced to be installed and run on the Windows 7 platform.

IDS-2200 Power Client Database Upgrade

The IDS-2200 1R2 Power Client has changed its use of database from Microsoft SQL Server 2000 Desktop Engine (MSDE) to Microsoft SQL Server 2008 Express.

IDS-2200 1R2 Security Agent LICENSE command

The IDS-2200 Security Agent Background Run has been enhanced to implement a new LICENSE command. The new command allows the site to view their license key information. The new LICENSE command output is:

*IDS LICENSE

IDSBG*072 The PRODUCT License is Licensed through Tue May 1 23:59:59 2012 IDSBG*073 using line#=1 Key=27C00E090004002C7283E2B2F000700B3 IDSBG*074 Partition Key for FCI480 FCI-PART-E; H8Y8TH1; IDSBG*007 LICENSE COMMAND COMPLETED.

IDS-2200 1R2 PME's for SILAS 2R5 and 3R2

The IDS-2200 Security Agent has been enhanced to provide new Product Modification Elements (PME's) for SILAS level's 2R5 and 3R2 with PME's SILAS2R5 and SILAS3R2 that are installed in SYS\$LIB\$*IDS-2.

IDS-2200 1R2 PME for MAPPER 46R1

The IDS-2200 Security Agent has been enhanced to provide a new Product Modification Elements (PME) for MAPPER 46R1 with PME's MAPPER46 that is installed in SYS\$LIB\$*IDS-2.

IDS-2200 Notes Of Interest

Only IDS-2200 Note of Interest (NOI) number 1 and above are relevant to level 1R2.

Restrictions and Limitations

Your environment must support UCS object module execution. This includes support for extended mode by the Exec as well as installation of the LINK and URTS products.

Compatibility and Migration

Release 1R2 is generated under CP OS2200 12.1

Previous Level Support

The prior level of IDS-2200 was 1R1. IDS-2200 1R1 will be supported until **12/31/2011**.

Documentation

Documents provided with release 1R2 includes:

IDS-2200 1R2 Security Agent Installation and Administrator Guide

IDS-2200 1R2 Power Client Installation and Administrator Guide

IDS-2200 Level 1R2 Release Announcement

IDS-2200 Quick Start Notes

OS2200 Release Tape Creation Instructions

FCI Website

You may obtain general information about Formula Consultants, Inc. and its products at our website at www.formula.com. After you register with the site and receive a userid and password, you can also download PCRs and Notes of Interest. Product documentation in PDF format is also available (Adobe Acrobat™ Reader required).

FCI Support Center

The FCI Support Center (FCISC) is available for use. The FCISC is a 2200 host server software system that is accessible by using the standard UNISYS Remote Site Support (RSS) product. It allows you to send and receive data electronically to and from FCI. Refer to the *IDS-2200 Security Agent Installation and Administrator Guide* for more information.

Corrections

File 13 on your release tape contains PCRs, if any, that have been generated against this release, as of the date your tape was created. Include any of these corrections applicable to your site with the first build from this tape. IDS-2200 elements are a combination of basic and UCS elements so the PCRs are organized by IDS-2200 processor type (basic mode or UCS). These elements can be @ADDed following an @COMUS to enter the corrections into your local COMUS database. Examine the file to determine which elements should be added to your build.

The elements README, CHGNUM-ALL, and IDS-NOIS are informational only and should not be @ADDed to your COMUS database.

The possible elements in File 13 are:

README explanation and cutoff date/time

ADD/SGS changes for the 'additional SGS' build prompt

BASE/version changes to IDS-2200 elements
CHGNUM-ALL list of all change numbers
IDS-NOIS all relevant Notes of Interest

where:

version can be BASIC or UCS depending on the associated IDS-2200 element. The CHG numbers generated by COMUS must be entered at the 'New Change number' build prompt. These numbers can be entered individually, or @ADD the CHGNUM elements that apply to your build.

If you add UCS corrections, the UCOB and/or UC compilers must be installed. Another method of including UCS corrections is to copy updated object modules contained in this file. This is done by answering the build prompt, 'Any replacement Object Modules to be included', and specifying the filename into which the modules were copied.

File 13 of your release tape also contains Notes of Interest in the element called IDS-NOIS. Notes of Interest are field bulletins which we recommend reading prior to generating or installing IDS-2200.

Ordering Instructions

General Releases

The OS2200 Software is included on the CD and is available in four different release tape formats, each in their own directory. The directory formats are:

DVD, DDP, FLIT and VTH.

Some sites will require a cartridge tape for a successful installation.

If **all** of the following are **true** for your site, please request the OS2200 components of IDS on cartridge tape.

- You are not running on a Dorado 300 series or above.
- You **do not** have DDP-FJT 5R5C (CP OS2200 9.0) or higher installed. It does not have to be running, it merely must be installed.
- You **do not** have FLIT 12R3 (CP OS2200 9.0) or higher installed.
- You **do not** have the Unisys VTH EXEC feature installed.
- You **do not** use or have RSS configured to run through the Internet, **and** your firewall **does not** allow you to send and receive on your port 102, with FCI's IP address.

Ordering the Software

To order your site's copy of IDS-2200 Level 1R2, contact a sales representative at Formula Consultants Inc. at **714-778-0123**

or complete the attached Product Order Form and fax it to 714-778-6364, or mail your order to:

Formula Consultants Incorporated P.O. Box 544 Anaheim, CA 92815 Attn: Product Sales

or Order IDS-2200 1R2 electronically by addressing your e-mail to:

sales@formula.com

or Order IDS-2200 level 1R2 through the Formula Consultants website at:

www.formula.com

Product Order Form

PRODUCT:	IDS-2200 Level 1R2		
CUSTOMER	::		
DELIVERY .	ADDRESS:		
CITY, STAT	Е:		
ZIP CODE:			
CONTACT:			
TELEPHONI	E NUMBER:		
LAST IDS-22	200 LEVEL RECEIVED:		
MEDIA - A	All tapes will be u	ınlabeled.	
Standard	d Media		
□ 18	3-track cartridge	☐ 36-track cartridge	\square DVD
□ El	ectronic via RSS and the	FCI Support Center	
Use S	SYS\$LIB\$*IDS.NEW-RE	ELEASE/RSS-SCRIPT to	copy to local tape.
Non-Star	ndard Media		
<u>suppl</u>		<u>er</u> , provided FCI has comp	(such as a 9840 A/B cartridge) patible equipment. Please contact FC media you are requesting.
Correction	ons		
Indic			your site minor corrections. uploading ASCII files from a PC to
□ 5 ⁻¹	¹ ⁄ ₄ " diskette	□ 360K	□ 1.2 mg
□ 18	3-track cartridge	☐ 36-track cartridge	
□ El	ectronic via RSS and the	FCI Support Center	